

# SAFETY DATA SHEET Linx Blue pigmented ink 1033

SECTION 1: Identification of the substance/mixture and of the company/undertaking		
1.1. Product identifier		
Product name	Linx Blue pigmented ink 1033	
Product number	1033	
1.2. Relevant identified uses of	of the substance or mixture and uses advised against	
Identified uses	Printing ink.	
1.3. Details of the supplier of the supplicit states and the supplicit states are supplied as the supplicit states are supplicit. The supplicit states are supplicit. The supplicit states are supplicit states are supplicit states are supplicit states are supplicit. The supplicit states are supplicit states are supplicit states are supplicit states are supplicit. The supplicit states are supplicit states are supplicit states are supplicit states are supplicit. The supplicit states are supplicit states are supplicit states are supplicit. The supplicit states are supplicit states are supplicit states are supplicit. The supplicit states are supplicit states are supplicit. The supplicit states are supplicit states are supplicit states are supplicit. The supplicit states are supplicit. The supplicit states are supplicit. The supplicit states are supplicit states are supplicit. The supplicit states are supplicit states are supplicit. The supplicit	the safety data sheet	
Supplier	Linx Printing Technologies Ltd	
	Linx House	
	8 Stocks Bridge Way	
	Compass Point Business Park	
	ST IVES	
	Cambridgeshire PE27 5JL UK	
	T: +44 (0)1480 302100 Mon-Fri 9am-5pm	
	F: +44 (0)1480 302116	
	E-mail: SDS@Linx.co.uk Web: www.linxglobal.com	
1.4. Emergency telephone number		
Emergency telephone	24HR: (+1)-352-323-3500; USA 1-800-535-5053	
SECTION 2: Hazards identification		
2.1. Classification of the subs	tance or mixture	
Classification (EC 1272/2008)		
Physical hazards	Flam. Liq. 2 - H225	
Health hazards	Eye Irrit. 2 - H319 STOT SE 3 - H336	
Environmental hazards	Not Classified	

### 2.2. Label elements

Hazard pictograms



Signal word	Danger
Hazard statements	H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Precautionary statements	<ul> <li>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P271 Use only outdoors or in a well-ventilated area.</li> <li>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</li> <li>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>P313 Get medical advice/ attention.</li> <li>P501 Dispose of contents/ container in accordance with national regulations.</li> </ul>
Contains	butanone
Supplementary precautionary statements	<ul> <li>P240 Ground and bond container and receiving equipment.</li> <li>P241 Use explosion-proof electrical equipment.</li> <li>P242 Use non-sparking tools.</li> <li>P243 Take action to prevent static discharges.</li> <li>P261 Avoid breathing vapour/ spray.</li> <li>P264 Wash contaminated skin thoroughly after handling.</li> <li>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.</li> <li>Rinse skin with water or shower.</li> <li>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</li> <li>P312 Call a POISON CENTRE/doctor if you feel unwell.</li> <li>P337+P313 If eye irritation persists: Get medical advice/ attention.</li> <li>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</li> <li>P403+P235 Store in a well-ventilated place. Keep cool.</li> <li>P405 Store locked up.</li> </ul>

# 2.3. Other hazards

None known.

# SECTION 3: Composition/information on ingredients

3.2. Mixtures		
BUTANONE		80-99.9%
CAS number: 78-93-3	EC number: 201-159-0	REACH registration number: 01- 2119457290-43-XXXX
Classification		
Flam. Liq. 2 - H225		
Eye Irrit. 2 - H319		
STOT SE 3 - H336		

The full text for all hazard statements is displayed in Section 16.

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

General information	Get medical attention if any discomfort continues. Never give anything by mouth to an unconscious person.
Inhalation	Move affected person to fresh air at once. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.

Ingestion	Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention immediately.	
Skin contact	Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.	
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.	
4.2. Most important symptoms	and effects, both acute and delayed	
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. See Section 11 for additional information on health hazards.	
Inhalation	Vapours may cause headache, fatigue, dizziness and nausea. Irritation of nose, throat and airway.	
Ingestion	May cause stomach pain or vomiting.	
Skin contact	Prolonged contact may cause redness, irritation and dry skin.	
Eye contact	May cause temporary eye irritation.	
4.3. Indication of any immediate medical attention and special treatment needed		
Notes for the doctor	If in doubt, get medical attention promptly. Treat symptomatically.	
SECTION 5: Firefighting measure	ures	
5.1. Extinguishing media		
Suitable extinguishing media	Extinguish with the following media: Alcohol-resistant foam. Carbon dioxide (CO2). Water spray, fog or mist. Powder.	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.	
5.2. Special hazards arising fro	om the substance or mixture	
Specific hazards	The product is highly flammable. Vapours may form explosive mixtures with air. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.	
Hazardous combustion products	Oxides of carbon. Oxides of nitrogen.	
5.3. Advice for firefighters		
Protective actions during firefighting	Control run-off water by containing and keeping it out of sewers and watercourses. Containers close to fire should be removed or cooled with water.	
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.	
SECTION 6: Accidental release		
	e measures	

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation of vapours. Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate.

## 6.2. Environmental precautions

**Environmental precautions** Do not discharge into drains or watercourses or onto the ground. Use appropriate containment to avoid environmental contamination.

## 6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: Contain and absorb spillage with sand, earth or other non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Collect and place in suitable waste disposal containers and seal securely.

#### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. For waste disposal, see Section 13.

# SECTION 7: Handling and storage 7.1. Precautions for safe handling Usage precautions Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Vapours may accumulate on the floor and in low-lying areas. Contaminated rags and cloths must be put in fireproof containers for disposal. 7.2. Conditions for safe storage, including any incompatibilities Storage precautions Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Storage class Flammable liquid storage. 7.3. Specific end use(s) Specific end use(s) The identified uses for this product are detailed in Section 1.2. SECTION 8: Exposure controls/Personal protection

### 8.1. Control parameters

### Occupational exposure limits

#### BUTANONE

Long-term exposure limit (8-hour TWA): WEL 200 ppm 600 mg/m<sup>3</sup> Short-term exposure limit (15-minute): WEL 300 ppm 899 mg/m<sup>3</sup> Sk WEL = Workplace Exposure Limit


Sk = Can be absorbed through the skin.

### **BUTANONE (CAS: 78-93-3)**

DNEL	Workers - Dermal; Long term systemic effects: 1161 mg/kg/day Workers - Inhalation; Long term systemic effects: 600 mg/m³
PNEC	Fresh water; 55.8 mg/l marine water; 55.8 mg/l Intermittent release; 55.8 mg/l Sediment (Freshwater); 284.7 mg/kg Soil; 22.5 mg/kg STP; 709 mg/l

### 8.2. Exposure controls

Protective	equipment
	ĮĮĮ.



#### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Blue.
Odour	Characteristic.
Odour threshold	Not available.
рН	Not available.
Melting point	-86°C
Initial boiling point and range	80°C @ 760 mm Hg
Flash point	-6°C Closed cup.
Evaporation rate	> BuAc (BuAc=1)
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 1.8 (%v/v) Upper flammable/explosive limit: 11.5 (%
Vapour pressure	78 mmHg @ 20°C
Vapour density	2.4

Relative density	0.82 - 0.96 @ 25°C
Solubility(ies)	Slightly soluble in water.
Partition coefficient	log Pow: 0.3 Information given is applicable to the major ingredient.
Auto-ignition temperature	515°C
Decomposition Temperature	Not available.
Viscosity	2 - 5 mPa s @ 25°C
Explosive properties	Not considered to be explosive.
Oxidising properties	Does not meet the criteria for classification as oxidising.
9.2. Other information	
Volatility	Volatile.
SECTION 10: Stability and rea	activity
10.1. Reactivity	
Reactivity	There are no known reactivity hazards associated with this product.
10.2. Chemical stability	
Stability	Stable at normal ambient temperatures.
10.3. Possibility of hazardous	reactions
Possibility of hazardous reactions	Will not polymerise.
10.4. Conditions to avoid	
Conditions to avoid	Avoid heat, flames and other sources of ignition.
10.5. Incompatible materials	
Materials to avoid	Strong acids. Strong alkalis. Strong oxidising agents. Strong reducing agents.
10.6. Hazardous decomposition	on products
Hazardous decomposition products	Does not decompose when used and stored as recommended.
SECTION 11: Toxicological in	formation
11.1. Information on toxicolog	ical effects
Acute toxicity - oral Notes (oral LD₅o)	Based on available data the classification criteria are not met.
<u>Acute toxicity - dermal</u> Notes (dermal LD₅₀)	Based on available data the classification criteria are not met.
Acute toxicity - inhalation Notes (inhalation LC <sub>50</sub> )	Based on available data the classification criteria are not met.
Skin corrosion/irritation	Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation Serious eye damage/irritation	Causes serious eye irritation.
Respiratory sensitisation	

Respiratory sensitisation	Based on available data the classification criteria are not met.	
Skin sensitisation Skin sensitisation	Based on available data the classification criteria are not met.	
Germ cell mutagenicity Genotoxicity - in vitro	Based on available data the classification criteria are not met.	
Carcinogenicity Carcinogenicity	Based on available data the classification criteria are not met.	
Reproductive toxicity Reproductive toxicity - fertility	Based on available data the classification criteria are not met.	
Reproductive toxicity - development	Based on available data the classification criteria are not met.	
Specific target organ toxicity -	single exposure	
STOT - single exposure	STOT SE 3 - H336	
Specific target organ toxicity - repeated exposure		
STOT - repeated exposure	Based on available data the classification criteria are not met.	
Aspiration hazard Aspiration hazard	Based on available data the classification criteria are not met.	
General information	The severity of the symptoms described will vary dependent on the concentration and the	
	length of exposure.	
Inhalation	length of exposure. Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting. Drowsiness, dizziness, disorientation, vertigo.	
Inhalation Ingestion	Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting. Drowsiness,	
	Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting. Drowsiness, dizziness, disorientation, vertigo. Liquid irritates mucous membranes and may cause abdominal pain if swallowed. Nausea,	
Ingestion	<ul> <li>Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting. Drowsiness, dizziness, disorientation, vertigo.</li> <li>Liquid irritates mucous membranes and may cause abdominal pain if swallowed. Nausea, vomiting. Diarrhoea.</li> <li>Product has a defatting effect on skin. Repeated exposure may cause skin dryness or</li> </ul>	
Ingestion Skin contact	<ul> <li>Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting. Drowsiness, dizziness, disorientation, vertigo.</li> <li>Liquid irritates mucous membranes and may cause abdominal pain if swallowed. Nausea, vomiting. Diarrhoea.</li> <li>Product has a defatting effect on skin. Repeated exposure may cause skin dryness or cracking.</li> </ul>	

# Toxicological information on ingredients.

## BUTANONE

Acute toxicity - oral	
Acute toxicity oral (LD₅₀ mg/kg)	2,737.0
Species	Rat
ATE oral (mg/kg)	2,737.0
Acute toxicity - dermal	
Acute toxicity dermal (LD₅₀ mg/kg)	6,480.0
Species	Rabbit

	ATE dermal (mg/	<b>vg)</b> 6,480.0			
	Acute toxicity - in	nalation			
	Acute toxicity inh (LC₅₀ vapours mg				
	Species	Rat			
	ATE inhalation (v mg/l)	apours 11,700.0			
SECTION 12: Ecological information					
Ecotoxicity		Not regarded as dangerous for the environment.			
12.1. Toxici	ty				
Toxicity		See the other subsections of this section for further details.			
Ecological in	nformation on ingre	dients.			
		BUTANONE			
	Acute aquatic tox	icity			
	Acute toxicity - fis	h LC₅₀, 96 hours: 2993 mg/l, Pimephales promelas (Fat-head Minnow)			
	Acute toxicity - ac invertebrates	uatic EC₅₀, 48 hours: 308 mg/l, Daphnia magna			
	Acute toxicity - ac plants	uatic EC₅₀, 72 hours: >100 mg/l, Pseudokirchneriella subcapitata			
12.2. Persis	tence and degrada	bility			
Persistence	and degradability	No data available.			
12.3. Bioaco	cumulative potentia	1			
Bioaccumul	ative potential	No data available on bioaccumulation.			
Partition coe	efficient	log Pow: 0.3 Information given is applicable to the major ingredient.			
12.4. Mobili	ty in soil				
Mobility		The product contains organic solvents which will evaporate easily from all surfaces.			
12.5. Result	ts of PBT and vPvE	assessment			
Results of F assessment	PBT and vPvB	This product does not contain any substances classified as PBT or vPvB.			
12.6. Other	adverse effects				
Other adver	se effects	None known.			
SECTION 13: Disposal considerations					
13.1. Waste treatment methods					
General info	ormation	When handling waste, the safety precautions applying to handling of the product should be considered. Materials such as cleaning rags and paper wipes that are contaminated with flammable liquids may self-ignite after use and should be stored in designated fireproof containers with tight-fitting, self-closing lids.			

Disposal methodsDispose of waste to licensed waste disposal site in accordance with the requirements of the<br/>local Waste Disposal Authority. Dispose of waste via a licensed waste disposal contractor.

Waste class	European Waste Catalogue Number (2000/532/EC): 08 03 12				
SECTION 14: Transport information					
14.1. UN number					
UN No. (ADR/RID)	1210				
UN No. (IMDG)	1210				
UN No. (ICAO)	1210				
14.2. UN proper shipping name					
Proper shipping name (ADR/RID)	PRINTING INK RELATED MATERIAL				
Proper shipping name (IMDG)	PRINTING INK RELATED MATERIAL				
Proper shipping name (ICAO)	PRINTING INK RELATED MATERIAL				
Proper shipping name (ADN)	PRINTING INK RELATED MATERIAL				
14.3. Transport hazard class(es)					
ADR/RID class	3 - F1				
ADR/RID label	3				
IMDG class	3				
ICAO class/division	3				
Transport labels					
14.4. Packing group					
ADR/RID packing group	II				
IMDG packing group	II				
ICAO packing group	II				
14.5. Environmental hazards					
Environmentally hazardous substance/marine pollutant No.					
14.6. Special precautions for u	ser				
EmS	F-E, S-D				
Emergency Action Code	3YE				
14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code					
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.				
SECTION 15: Regulatory information					
15.1. Safety, health and enviro	15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture				

### National regulations

Control of Substances Hazardous to Health Regulations 2002 (as amended).

EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Commission Regulation (EU) No 2015/830 of 28 May 2015. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Guidance	Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37.
Authorisations (Annex XIV Regulation 1907/2006)	No specific authorisations are known for this product.
Restrictions (Annex XVII Regulation 1907/2006)	No specific restrictions on use are known for this product.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet	•
Revision date	03/09/2019
Revision	7
Supersedes date	10/12/2015
SDS number	10272
Hazard statements in full	H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.