

GP-X CLASSIC | VALVE ACTION | ALL PURPOSE PAINT MARKER

Xylene

FEATURES:

- Valve Action markers allow control of paint flow while keeping the paint in the barrel from drying-out when the cap is off.
- Replaceable tips extend the life of your markers.
- Clearly marks on dark or light surfaces.
- Great for metal, wood, corrugated, rubber, plastic, glass and other hard to mark surfaces.
- Available in 13 weather & fade resistant colors.
- Sold by color in boxes of 12. Cartons include 12 boxes / 144 markers.

COMPATIBILITY:

- Safe for most porous & non-porous surfaces.
- Test on surfaces prior to use to ensure compatibility.

DIRECTIONS FOR USE:

- Shake marker well with the cap on
- Twist the cap off
- Gently pump until the tip is primed

HEALTH & SAFETY:

- Use only with proper ventilation.
- Flammable liquid & vapor: keep away from ignition sources like flames, sparks, or electrostatic charges.
- Avoid skin and eye contact and ingestion.
- For complete health & safety data, refer to SDS at www.diagraphmsp.com

TECH SPECS:

- Standard Stroke Width: 1/8"
- Fill Quantity: ~1/2 oz (~12 cc)
- Barrel Size: .563" Diameter x 4.75" Long

PHYSICAL PROPERTIES:

Color	Part No.	Specific Gravity	VOC Level	Flash Point	Resistant to	Approx. Dry Time
Black	0918500	0.971	6.5 lbs/gal	75.2°F (24.0°C)	750°F	20-30 Sec
Yellow	0958500	1.030	5.9 lbs/gal	75.2°F (24.0°C)	750°F	20-30 Sec
White	0968500	1.284	5.6 lbs/gal	75.2°F (24.0°C)	750°F	20-30 Sec
Blue	0968521	1.147	5.3 lbs/gal	75.2°F (24.0°C)	700°F	20-30 Sec
Red	0968520	1.043	5.6 lbs/gal	75.2°F (24.0°C)	750°F	20-30 Sec
Green	0968522	1.175	5.5 lbs/gal	75.2°F (24.0°C)	750°F	20-30 Sec
Orange	0968523	1.088	5.2 lbs/gal	75.2°F (24.0°C)	750°F	20-30 Sec
Silver	0968524	0.921	6.4 lbs/gal	75.2°F (24.0°C)	1000°F	20-30 Sec
Pink	0968526	1.215	5.5 lbs/gal	75.2°F (24.0°C)	650°F	20-30 Sec
Purple	0968527	1.237	5.4 lbs/gal	75.2°F (24.0°C)	700°F	20-30 Sec
Light Green	0968528	1.237	5.6 lbs/gal	75.2°F (24.0°C)	700°F	20-30 Sec
Gold	0968529	1.102	5.9 lbs/gal	75.2°F (24.0°C)	N/A	20-30 Sec
Brown	0968530	1.085	4.4 lbs/gal	75.2°F (24.0°C)	750°F	20-30 Sec